


# Specifications

MODELS	IWP™-20S		IWP™-25S		IWP™-30S	
	US	Metric	US	Metric	US	Metric
Working height*	26 ft 6 in	8.24 m	30 ft 5 in	9.44 m	35 ft 6 in	11 m
Platform height	20 ft 6 in	6.24 m	24 ft 5 in	7.44 m	29 ft 6 in	9 m
A Horizontal outreach**	2 ft 2 in	.66 m	—	—	—	—
B Height - stowed:						
fully lowered	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m
base raised	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
C Length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
D Width - standard base	2 ft 8 in	.81 m	2 ft 8 in	.81 m	—	—
wide base	3 ft 4 in	1.02 m	3 ft 4 in	1.02 m	3 ft 4 in	1.02 m
Corner access***	6 in	.15 m	6 in	.15 m	7 in	.18 m



## PRODUCTIVITY

Lift capacity: ANSI/CE	350 lbs	159 kg	350 lbs	159 kg	350 lbs	159 kg
CSA	300 lbs	136 kg	300 lbs	136 kg	—	—
With outreach option	300 lbs	136 kg	—	—	—	—
Platform Dimensions (l/w/h)						
Standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated ultra narrow**	22/18/44.75 in	56/46/114 cm	22/18/44.75 in	56/46/114 cm	22/18/44.75 in	56/46/114 cm
Gated narrow	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm
Front entry gated narrow	20/26/44.75 in	51/66/114 cm	20/26/44.75 in	51/66/114 cm	20/26/44.75 in	51/66/114 cm
Front/side entry extra-large**	30/28/44.75 in	76/71/114 cm	30/28/44.75 in	76/71/114 cm	30/28/44.75 in	76/71/114 cm
Standard fiberglass**	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm
Narrow fiberglass**	26/22/43.5 in	66/56/110 cm	26/22/43.5 in	66/56/110 cm	26/22/43.5 in	66/56/110 cm

## POWER

AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V / 110 V / 60 Hz or 110/230 Hz worldwide model

## WEIGHT\*\*\*\*

Standard base						
ANSI (AC)	1,245 lbs	565 kg	1,290 lbs	585 kg	—	—
ANSI (DC)	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—
CE (AC)	1,245 lbs	565 kg	1,290 lbs	585 kg	—	—
CE (DC)	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—
CSA (AC)	1,633 lbs	741 kg	—	—	—	—
CSA (DC)	1,733 lbs	786 kg	—	—	—	—

Standard base with outreach option						
ANSI (AC)	1,350 lbs	612 kg	—	—	—	—
ANSI (DC)	1,450 lbs	658 kg	—	—	—	—
CE (AC)	1,350 lbs	612 kg	—	—	—	—
CE (DC)	1,450 lbs	658 kg	—	—	—	—

Wide base						
ANSI (AC)	1,345 lbs	610 kg	1,390 lbs	630 kg	1,430 lbs	649 kg
ANSI (DC)	1,445 lbs	655 kg	1,490 lbs	676 kg	1,530 lbs	694 kg
CE (AC)	1,345 lbs	610 kg	1,390 lbs	630 kg	1,430 lbs	649 kg
CE (DC)	1,445 lbs	655 kg	1,490 lbs	676 kg	1,530 lbs	694 kg
CSA (AC)	1,525 lbs	692 kg	1,880 lbs	853 kg	—	—
CSA (DC)	1,625 lbs	737 kg	1,980 lbs	898 kg	—	—

Wide base with outreach option						
ANSI (AC)	1,450 lbs	658 kg	—	—	—	—
ANSI (DC)	1,550 lbs	703 kg	—	—	—	—
CE (AC)	1,450 lbs	658 kg	—	—	—	—
CE (DC)	1,550 lbs	703 kg	—	—	—	—
CSA (AC)	1,633 lbs	741 kg	—	—	—	—
CSA (DC)	1,733 lbs	786 kg	—	—	—	—

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Gated ultra narrow and fiberglass platforms are not available with the outreach option.

\*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

\*\*\*\* Weight will vary depending on options and/or country standards.

**STANDARDS COMPLIANCE** ANSI A92.3, CSA B354.1, CE Compliance, AS 1418.10

## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated ultra narrow platform
- Gated narrow platform
- Standard fiberglass platform
- Narrow fiberglass platform

#### POWER OPTIONS

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz worldwide model
- Power assist option

#### BASE OPTIONS

- Standard base (IWP-20S and 25S only)
- Wide base

### STANDARD FEATURES

#### MEASUREMENTS

##### IWP™-20S

- 26 ft 5 in (8.22 m) working height
- 20 ft 5 in (6.22 m) platform height
- 2 ft 8 in (.81 m) standard base width
- 3 ft 4 in (1.02 m) wide base width
- Outreach option adds 2 ft 2 in (.66 m) of horizontal reach
- Up to 350 lb (159 kg) lift capacity

##### IWP™-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

##### IWP™-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

#### PRODUCTIVITY

- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Choose from standard or wide base
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Tie down attachment points
- Overhead crane attachment points
- Wide forklift pockets
- Built-in level sensing with interlocks

#### POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system



### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Gated standard platform
- Gated ultra narrow platform
- Gated narrow platform
- Standard fiberglass platform (not available with outreach)
- Narrow fiberglass platform (not available with outreach)
- Outreach option (IWP-20S only)
- Operational working light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

#### POWER

- Power wheel assist with dual battery package\*
- Dual battery package

\* Adds 12.5 in (.32 m) to unit length and 285 lbs (129 kg) to unit weight